

#### Aritco 7000

The lift is designed to meet all requirements for quality, safety and service life. It is a perfect fit for tough and demanding environments such as schools, shops and residential buildings.

#### Several advantages offered by Aritco 7000:

- Design, sizes and options tailored for public environments
- 95% recyclable materials
- 'A' rated energy consumption according to VDI4707
- Patented screw/nut technology (no oil that can leak)
- The lowest maintenance and operating costs on the market

For more information visit: aritcoplatformlifts.com/7000

CONTACT US: 088-333-2020 088-333-5050

088-333-9090



ARITCO (THAILAND) Co., Ltd. 130/3 Thientalay 24, Bangkhunthien-Chaytalay, Takham, Bangkhunthien, Bangkok 10150, Thailand Tel: 02-408-0200 Fax: 02-683-8877

www.aritcothailand.com, facebook.com/Aritcothailand



## Aritco 7000

#### LIFT COLOUR .....

Can be painted in any RAL colour from the RAL Classic chart.



#### GLASS .....

4 different glass types to choose from.











#### FLOOR .....

9 different floorings to choose from.




















## 1190 0 1040


**Size:** 900 x 1040 mm **Rated load:** 250 kg / 2 pers.

Wheelchair: -




**Size:** 900 x 1480 mm

Rated load: 410, 500 kg / 5, 6 pers. Wheelchair: A or B with attendent\*



**Size:** 1000 x 1480 mm

Rated load: 410, 500 kg / 5, 6 pers. Wheelchair: A or B with attendent\*




**Size:** 1000 x 1980 mm **Rated load:** 500 kg / 6 pers.


Wheelchair: A or B with attendent\*

1430 O 1280 1330

Size: 900 x 1280 mm Rated load: 410 kg / 5 pers. Wheelchair: Lone user or type A\*




Size: 1000 x 1280 mm Rated load: 410 kg / 5 pers. Wheelchair: Lone user or type A\*



**Size:** 1100 x 1480 mm

Rated load: 410, 500 kg / 5, 6 pers.

Wheelchair: A or B with attendent, adjacent entry\*



Size: 1100 x 1580 mm Rated load: 500 kg / 6 pers. Wheelchair: A or B with attendent, adjacent entry\*

\* National guidelines may apply. Wheelchair Type A and B according to EN 12183/EN 12184.

#### Product summary

## Minimum 1100 mm



#### INSTALLATION

Recessed installation 50 mm below floor Installed directly on floor with 50 mm ramp

**Control voltage** 

24 V

#### TYPE OF LIFT

Platform lift intended for installation in public environments.



RATED SPEED

Max. **0,15 m/s** 

# DRIVE

DRIVE SYSTEM

Patented screw and nut system

2.2 kW motor

### TRAVEL HEIGHT

250–13000 millimeter

## CONTROL FROM CARRIER CONTROL PANEL

Hold to run – press and hold For installations outside Europe One touch operation (press one time)



2 to 6 floors



#### WARRANTY

Aritco 7000 comes with a 24 months warranty. The screw and nut assembly has a 10 year warranty.



## TECHNICAL COMPLIANCE

European Machine directive 2006/42/EC European standard EN 81-41

Emergency lowering: Battery-powered