*CCESSIBILITY FOR HXME & PUBLIC BUILDINXS

Aritco Home & Public Access Lift

Datasheet 2021

Aritco Access Lift is designed to make your home as well as public and commercial buildings accessible for everyone. Practical and smart with sizes for all needs. The lift expresses Scandinavian design and features a backlit panel and lit handlebar. With an option to personalize it with details such as glass walls, a range of various colors and different materials.

Advantages offered by Aritco Access Lift:

- Design, sizes and options created for a home environment
- Minimum interventions in the house
- Option for a "half-height door" on the top floor
- 'A' rated energy consumption according to VDI4707
- 95% recyclable materials
- Patented screw/nut technology (no oil that can leak)
- The lowest maintenance and operating costs on the market
- Equipped with our SmartSafety system with safety features for home environments.

For more information please visit: www.aritco.co.th











CONTACT US: 088-333-2020 088-333-5050 088-333-9090

ARITCO (THAILAND) CO., LTD.


467/2, Rama 3 Rd., Bang Khlo, Bang Kho Laem, Bangkok Thailand 10120 Tel: 02 - 408 - 0200 Fax: 02 - 638 - 8877

Website: www.aritco.co.th



ARITCO ACCESS LIFT





Size: 900 x 1040 mm **Rated load:** 250 kg / 2 pers.


1600

1480


Wheelchair: -

900


Size: 900 x 1480 mm



Size: 900 x 1280 mm Rated load: 410 kg / 5 pers. Wheelchair: Lone user or type A*




Size: 1000 x 1280 mm Rated load: 410 kg / 5 pers. Wheelchair: Lone user or type A*




Size: 1100 x 1480 mm **Rated load:** 410, 500 kg / 5, 6 pers.

Wheelchair: A or B with attendent, adjacent entry*




Rated load: 410, 500 kg / 5, 6 pers.

Size: 1000 x 1480 mm Rated load: 410, 500 kg / 5, 6 pers. Wheelchair: A or B with attendent*



Size: 1000 x 1980 mm Rated load: 500 kg / 6 pers. Wheelchair: A or B with attendent*



Size: 1100 x 1580 mm Rated load: 500 kg / 6 pers. Wheelchair: A or B with attendent, adjacent entry*

* National guidelines may apply. Wheelchair Type A and B according to EN 12183/EN 12184.

Dark Grey, Vinyl

Light Grey, Vinyl

Aged Oak, Vinyl

Oiled Oak, Vinyl

Checker Stud Grey, Rubber

Product summary

TOP HEIGHT Minimum

Power supply:

230 V 1-phase: Max 0,15 m/s 400 V 3-phase : Max 0,25 m/s

(outside Europe)



DRIVE SYSTEM

Patented screw and nut system 2.2 kW motor



CONTROL PANEL

One touch operation

(press one time)

Hold to run - press and hold For installations outside Europe

WARRANTY

CONTROL FROM CARRIER

Aritco access lift comes with a 24 month warranty. The screw and nut assembly has a 10 year warranty.



2 to 6 floors



Recessed installation 50 mm below floor

INSTALLATION Installed directly on floor with 50 mm ramp

TRAVEL HEIGHT 250 - 13000millimeter



TECHNICAL COMPLIANCE

European Machine directive 2006/42/EC European standard EN 81-41

Emergency lowering: Battery-powered