

Aritco HomeLift

We know every home is unique, and your home is a special place for you. You have picked every colour, every piece of furniture and every bit of decoration to create a home that is designed for your family, for your life and for your comfort.

Aritco HomeLift is designed to be that extra feature of your home. It is decorative and is a spectacular design feature, which makes your home unique. It provides you with that extra feeling of luxury, and it ignites the full potential of your home.

For more information visit: aritcohomelifts.com

CONTACT US: 088-333-2020 088-333-5050

088-333-9090



ARITCO (THAILAND) Co., Ltd.
130/3 Thientalay 24, Bangkhunthien-Chaytalay,
Takham, Bangkhunthien, Bangkok 10150, Thailand
Tel: 02-408-0200
Fax: 02-683-8877

www.aritcothailand.com, facebook.com/Aritcothailand
















installed in the lift walls on each floor. The doors are double doors, i.e. two leaves with a central opening. The door leaves are made of glass with painted profiles.




Size: 1100 x 1400 mm Rated load: 400 kg / 5 pers.




Size: 600 x 830 mm Rated load: 250 kg / 2 pers.



Size: 1000 x 830 mm



Size: 1100 x 830 mm Rated load: 250 kg / 3 pers. Rated load: 250 kg / 3 pers.



Size: 1000 x 1200 mm Rated load: 400 kg / 5 pers.

Product summary

TOP HEIGHT

inimum



INSTALLATION

Recessed installation 37 mm below floor Installed directly on floor with 37 mm ramp

TYPE OF LIFT

Home lift intended for installation in private homes.



RATED SPEED

Max **0,15 m/s** (inside Europe) Max **0,30 m/s** (outside Europe)



SYSTEM Screw and nut

system

TRAVEL HEIGHT

250–15 000 milli<u>meter</u>

CONTROL FROM CARRIER CONTROL PANEL

Hold to run - press and hold For installations outside Europe One touch operation (press one time)



WARRANTY

Aritco HomeLift comes with a 24 months warranty. The screw and nut assembly has a 10 year warranty.



TECHNICAL COMPLIANCE

European Machine directive 2006/42/EC European standard EN 81-41